



## PCI-X power with analog video capture.

The Osprey 230 analog video capture card offers legendary Osprey® quality and reliability, designed for streaming professionals. It's the ideal PCI-X™ analog card for broadcast professionals and global OEM systems integrators. With its composite and S-Video inputs and professional balanced audio features, it's the card of choice for high quality, reliable video capture.

### Industry proven performance.

More than 400K Osprey cards are being used globally in a variety of broadcast, commercial and industrial applications. You'll find Osprey cards in mission-critical applications throughout the world.

### Multiple streams per input.

Purchase the Osprey 230 with SimulStream® and you can feed audio and video to multiple encoders at the same time. Or, create multiple streams of the same type with completely independent settings for sizing, scaling, logos and bit rate.

### Software compatible.

The Osprey 230 works with popular video capture and encoding applications to provide maximum flexibility in meeting the requirements of your unique application.

#### Ideal Solutions

- > Broadcasters
- > Enterprise
- > Government
- > OEM systems integrators

#### Applications

- > Webcasting
- > Live streaming
- > Podcasting
- > Mobile TV
- > Video on Demand
- > Surveillance

#### Key Attributes

- > Enables multiple Osprey 230 cards per chassis
- > Supports global analog standard-definition formats, including NTSC and PAL
- > Automatically detects and adapts on-the-fly when the input video format changes from movie frame rates to television frame rates
- > Provides automatic optimization for changing motion content
- > Includes logo/bitmap overlay with transparency and positioning controls
- > Captures full-frame video at 30 frames per second providing full standard-definition resolution for maximum quality
- > PCI-X compatible
- > Provides audio loop-back output
- > Drivers available for Microsoft® Windows® operating systems

## OSPREY® 230

Video Capture Card

**Breakout Cable**  
(included)



**Breakout Panel**  
(optional)



### Driver Support:

- Microsoft® DirectShow® API

### Inputs:

Video:

One channel switchable input:

- Composite (BNC x 1)
- S-Video (mini-DIN)

Audio:

- Balanced stereo (XLR x 2)
- Unbalanced stereo (RCA x 2)

### Outputs:

Audio:

- Unbalanced stereo line (3.5 mm)

### Video Format:

- NTSC/PAL

### Pre-Processing:

- Closed-caption extraction/rendering
- Software-adjustable hardware audio gain control
- Logo/bitmap overlay
- Scaling, cropping, de-interlacing and inverse telecine
- Loss of video automatic test pattern generation with text overlay option

### Dimensions:

- Half-height / half-length board
- 6.60" L x 2.71" H  
(16.77 cm L x 6.87 cm H)
- 64-bit PCI™ interface
- 32-bit/33-MHz PCI compatible
- 3.3 V PCI 2.3 compliant
- Includes low-profile bracket

### Hardware Warranty:

- 1 year limited hardware warranty

### System Requirements:

- Multi-core processors are recommended to run video applications.



© 2011 ViewCast Corporation. ViewCast®, Niagara®, Osprey®, SimulStream®, SchedulStream®, GoStream®, EZStream®, VMp™ and Niagara® SCX (and design)™ are registered trademarks of ViewCast Corporation or its subsidiaries. All other trademarks are the property of their respective owners. Product specifications and availability may change without notice.

US/Canada 800.250.6622 | Europe/Middle East/Africa +44 1256 345610 | Asia/Pacific +852 2251 8778

Visit us on the web at [www.viewcast.com](http://www.viewcast.com)